

FireShield Foam Extinguisher

Product Specification Sheet

FireShield



Key Features

- CE approved
- Kitemarked to BS EN3 (6 & 9ltr models)
- Manufactured to BS EN3
- MED approved (6 & 9ltr models)
- Passed 35kv conductivity test
- Polythene internal lining
- Corrosion resistant finish
- Full range of spare parts available
- Brass spray nozzle (1ltr model)
- Hose assembly (3, 6 & 9ltr models)
- Transport bracket included (1 & 2ltr models)
- J bracket included (3, 6 & 9ltr models)
- Super strong base skirt for protection (6 & 9ltr models)
- Squeeze grip operation
- Built to last –ideal for harsh environments
- 5 year warranty on all models



The FireShield Foam extinguishers quickly tackle Class B fires and keep visibility clear, unlike water units. Covers Class A and B fires, meets top European standards, and includes a 5 year warranty. Lightweight, compact, and corrosion-resistant, it comes with a wire bracket and replacement parts.



Technical Specifications

Specifications	FO001/001	FO001/002	FO001/003	FO001/004	FO001/006
Capacity	1ltr	2ltr	3ltr	6ltr	9ltr
Fire Rating	5A 21B	8A 55B	13A 70B	21A 144B	27A 183B
Extinguishing	AFFF	AFFF	AFFF	AFFF	AFFF
Working Pressure	14 Bar	12 Bar	12 Bar	14 Bar	12 Bar
Temperature Range	+5°C - +60°C	+5°C - +60°C	+5°C - +60°C	+5°C - +60°C	+5°C - +60°C
Cylinder Material	Steel	Steel	Steel	Steel	Steel
Pressuring Gas	Nitrogen	Nitrogen	Nitrogen	Nitrogen	Nitrogen
Height	337mm	405mm	450mm	515mm	637mm
Width inc. Hose	115mm	153mm	235mm	265mm	265mm
Diameter	100mm	115mm	140mm	175mm	210mm
Weight	2.0kg	3.9kg	5.3kg	9.3kg	19.4kg